

Scan and Login website for more information

Guilin Woodpecker Medical Instrument Co., Ltd.

Information Industrial Park, Guilin National High-Tech Zone, Guilin, Guangxi, 541004 P.R. China

Tel: +86-773-5873196 +86-773-2035099


Fax: +86-773-5824250

E-mail: woodpecker@guilindental.com

Website: www.guwoodpecker.com

MedNet GmbH Borkfaktorie 10-48163 Muenster-Germany

DISTRIBUTED BY:



2019/06-10-103



The choice of millions of dentists worldwide

A New Generation of High Power Dental Diode Lasers



LX16

Guilin Woodpecker Medical Instrument Co., Ltd.

Wide scope of application

Can be used for the fields of dental soft tissue surgery, endodontic sterilization, periodontal sterilization, peri-implantitis, low intensity laser therapy, oral ulcer, and teeth whitening.

Remarkable treatment effect:

There is basically no bleeding during operation, maximally minimizing the postoperative swelling, reducing pain of patients, and accelerating the recovery.



Before treatment



Under treatment



Four weeks later

Intelligent human-machine interaction

5-inch full-view capacitive touch panel with flat UI design



High Power

Up to 16W (Peak Power) laser output with wavelength of 976nm and additional 200mW laser output with wavelength of 650nm, which covers more than 20 indications.

LX16

Effective prevention of cross-infection

The fiber-optical tips and Stainless handpiece sleeve can be autoclaved.



Large-capacity battery

11.1V 2600mAh x2 (57.7Wh) lithium battery, which can be used for one week on a single charge.



Complete accessories

Fiber-optical tips, TMJ therapy tip, whitening tip, biostimulation tip, laser protective glasses



Effective prevention

Three pairs of laser protective glasses can effectively prevent the dentist, assistant and patient from laser radiation.



Metal handle enables flexible movements.

Laser parameters

- Wavelengths & optical power:
 - 976 ± 20 nm : Pmax=16W
 - 650 ± 20 nm : Pmax=200mW
- Laser system:
 - 976 nm: Class IV
 - 650 nm: Class II (according to IEC 60825-1)
- Emission modes:
 - CW (continuous wave), chopped 1 Hz to 20 kHz
- Aiming beam:
 - 650 ± 20 nm / Pmax<5mW
- Battery:
 - 11.1V 2600mAh x2 (57.7Wh)

